

**FATHOM**  
D I V E S Y S T E M S

3rd GEN PITKIN CONTROLLER  
USER MANUAL



---

## 3rd Gen Pitkin Controller

The 3rd gen Pitkin Controller can be used to adjust the power on a heated vest, habitat scrubber, or other battery powered device. The power controller is connected inline between the battery pack and the powered device using e/o cords and uses tap or switch control to select one of six power settings (0, 20, 40, 60, 80, or 100%). An LED indicates the current power setting. The power controller is rated for 5-24 v input but doesn't regulate voltage at a constant output so divers must verify the heated vest or device being powered can handle the battery voltage. The power controller is rated for 10 amps at any voltage.

**When connecting the power controller, be sure to connect the e/o cord with the red band to the power supply.**

## Output Level

The LED flashes indicate power output level.

Flashes	Power Level
Solid LED	100%
4	80%
3	60%
2	40%
1	20%
0	Off

## Tap Control

The LED flashes red every time a tap is detected and flashes an equivalent number of flashes after 5, 6, or 7 taps are detected (less than 1/3 second apart).

Taps	Function
3	increases power
2	decreases power
5	sets tap sensitivity (see below)
6	toggles power interruption control (see below)
7	toggles between standard suit heater mode (blue LED) and motor control mode (green LED, see below)

---

## Set Tap Sensitivity

- 5 taps ► LED indicator changes to red.
- Adjust tap sensitivity from level 0 to 5 using 2 or 3 taps. Most people can leave at the default 100%.
- 5 taps to save and exit.
- Tap sensitivity is always at 100% for 5 seconds after the controller is powered up to allow this menu to be entered.
- Output power is switched off while tap sensitivity is being adjusted.

## Motor Control Mode

(for habitat scrubber fan motors)

- Uses higher frequency (20kHz) pulse width modulation (PWM) and different power settings optimised for that purpose.
- Much less efficient for heat control than suit heater mode which uses 20Hz PWM.
- Switch between motor control (green LED) and suit heater mode (blue LED) with 7 taps.

## Power Interruption Control

- Briefly interrupt (off/on) the power to go down one power level.
- Switch off for 3-5 seconds to revert to full power.
- This mode can be enabled/disabled by 6 taps.



**FATHOM**  
D I V E S Y S T E M S

**FATHOM DIVE SYSTEMS LLC**

4113 NW 6th St, Suite A, Gainesville, FL 32609

+1 352 213 8486

[info@fathomdive.com](mailto:info@fathomdive.com)

[www.fathomdive.com](http://www.fathomdive.com)